فلیت خراب تریلر



(Picture is mentioed for the reference only)

TYPE DESIGNATION 3-AXLE STANCHION PLATFORM TRAILER

Lightweight frame made from special high-strength steel.

Steel stud plate floor, 5/7 mm, tack-welded.

Installation of axles from well-known manufacturers.

OPTIONAL: Installation of Extensions 1.5 ft on each side

OPTIONAL: Heavy-duty band winch with 10 m belt incl. triangle and clamp OPTIONAL: Mudguard easily removable

OPTIONAL: Side Support Pillars OPTIONAL: Floor Extra Channels

OPTIONAL: Rear Lights

OPTIONAL: Mudguards with spray protection

OPTIONAL: Wheel Chocks

FRAME

Welded steel frame construction Reinforced external lashing frame Low-maintenance ball bearing turntable 11 pairs of recessed lashing points

Reflective contour marking strips across entire length of sides and on the rear

DRAWGEAR

Fixed drawbar, 40 mm

SPECIFICATIONS	AGM/T/ <mark>36</mark> T
Size: Overall Vessel Length Overall Vessel Width Overall Sides Height Bed Sheet Gauge:	10.9m / 36ft 2m / 7ft 1.2m / 4ft SWG 10
Side Sheet Gauge:	SWG 10
Axle Size with Hub:	5" x 8mm
Cross (Floor) Channel Size:	5 Inches
Main Channel Size:	12 Inches
Tyre Size:	1100-20 / 1000-20
Total Number of Wheel Rims:	12
Number of Axle:	03 with Front has Turntable 360 Degree
Weight (Without Load):	2500 KG
Loading Capacity:	36 Ton
Tractor Compatibility:	88hp — 120hp
Paint:	2 coats of desired shade of antirust paint with Zn Oxide Primer Paint.
Accessories:	Tool Box

Email: agro1@metron.af Website: www.metron.af