



ایگرو1 agro1

A Project By Metron International

INTER-ROW MULCHER

د قطار بین المللی



Rhodes grass is a perennial or annual tropical grass. It is a leafy grass, 1-2 m in height, highly variable in habit. The culms are tufted or creeping, erect or decumbent, sometimes rooting from the nodes. Inter Row Rotary Tiller is a tractor operated implement which is similar to rotator but it covers only in between crop rows and it is specially designed for mulching of crop residue into the soil. Rotor assembly is easily detachable as per crop row spacing.

DETAILS	MODELS			
	AGM/IRM-2	AGM/IRM-4	AGM/IRM-5	AGM/IRM-6
Power Requirements	40 — 60 HP	75 — 90 HP	90 — 110 HP	90 — 110 HP
Number of Rows	2	4	5	6
Capacity	5-6 Acre per day	6-7 Acre per day	7-8 Acre per day	7-8 Acre per day
Inter-row Distance Range, adjustable as per crop row spacing	450 mm — 760 mm (Approx.)			
No. of Tines in each spade	16			
Gear Box	Single Stage			
Gear Box Oil	SAE 140			
Drive Transmission	Hexagonal Shaft			
Rotor Diameter	480mm			
Rotor Speed	218 RPM			
PTO Speed	540 RPM and Required Standard Six Splines input shaft			

PARK E SANATI PUL E CHARKHI KABUL JALALABAD HIGHWAY
KABUL AFGHANISTAN

پارک سنّتی پل چرخي کابل جلال اباد لويه لار کابل افغانستان

Ph: +93 788 888608, +93 799 868606
+93 799 727313, +93 799 869786

Email: agro1@metron.af

Website: www.metron.af